Creation Date : March 31, 1993 Revision Date : December 17, 2010 Issue Date :

# MATERIAL SAFETY DATA SHEET(JURA Model)

# 1. CHEMICAL PRODUCT & COMPANY IDENTIFICATION

PRODUCT NAME	: TDI - 80	
PRODUCT CODE	:	
COMPANY IDENTIFICATION		
Company name	: Japan Urethane Raw Materials Association	
Address	:	
Department	:	
Telephone	:	
Emergency telephone	:	
Fax	:	
e-mail address	:	
MSDS No.	: 0331	

RECOMMENDED USE OF THE CHEMICAL AND RESTRICTIONS ON USE :

The main use is polyurethane raw materials (flexible and semi rigid foam, rigid foam, elastomer, artificial leather and synthetic leather, spandex fiber, paint, glue, binder, etc.).

## 2. HAZARD IDENTIFICATION

GHS CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

PHYSICAL HAZARDS

•	Explosives	: Not applicable
•	Flammable gases	: Not applicable
•	Flammable gases	: Not applicable
•	Flammable aerosols	: Not applicable
•	Oxidizing gases	: Not applicable
•	Gases under pressure	: Not applicable
•	Flammable liquids	: Not classified
•	Flammable solids	: Not applicable
•	Self-reactive substances and mixtures	: Not applicable
•	Pyrophoric liquids	: Not classified
•	Pyrophoric solids	: Not applicable
•	Self-heating substances and mixtures	: Not applicable
•	Substances and mixture which, in contact with wat	er, emit flammable gases
		: Not classified
•	Oxidizing liquids	: Not classified
•	Oxidizing solids	: Not applicable
•	Organic peroxides	: Not applicable

Corrosive to metals : Not classified	
HEALTH HAZARDS	
Acute toxicity (oral)	: Not classified
Acute toxicity (oral)	: Not classified
• Acute toxicity (skin)	: Not classified
• Acute toxicity (inhalation: gas)	: Not applicable
• Acute toxicity (inhalation: vapour)	: Category 1
• Acute toxicity (inhalation: dust, mist)	: Not applicable
Skin corrosion / irritation	: Category 2
Serious eye damages / eye irritation	: Category 2A
Respiratory sensitization	: Category 1
Skin sensitization	: Category 1
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity single exposure	: Category 3 (respiratory tract irritation)
Specific target organ toxicity: repeated exposure	: Not classified
Aspiration hazard	: Not classified
ENVIRONMENTAL HAZARDS	
• Aquatic toxicity (acute)	: Category 3
Aquatic toxicity (chromic)	: Not classified

# GHS LABEL ELEMENTS INCLUDING PRECAUTIONARY STATEMENTS

SYMBOL





# SIGNAL WORD : DANGER

HAZARD STATEMENT

- Fatal if inhaled.
- Causes skin irritation.
- Causes serious eye irritation.
- May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- May cause allergic skin reaction.
- Irritation to the respiratory system.
- Harmful to aquatic life.

# PRECAUTIONARY STATEMENTS:

# [Prevention]

- Do not handle until all safety precautions have been read and understood.
- Obtain special instructions before use.
- Do not eat, drink or smoke when using this product.

- Wear protective gloves/goggles/clothing and respiratory protection.
- Use only outdoors or in well-ventilated area.
- Do not breathe dust/fume/gas/mist/vapors/spray.
- Wash hands thoroughly after handling.
- · Contaminated work clothing should not be allowed out of workplace.
- Avoid release to the environment.
- Avoid contact with water and alkali.
- Do not use near fire.

## [Response]

- If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- · If swallowed: Rinse mouth with water. Do not induce vomiting.
- · If in eyes: Rinse with water for 15 minutes. Remove contact lenses, if present and easy to do.
- · If on skin: Wash with plenty of soap and water.
- If on skin (or hair): Remove all contaminated clothing.
- Wash contaminated clothing before re-using.
- IF exposed or concerned, or if you feel unwell: Get medical advice/attention.
- Dry chemical powder should be used for small fire. In case of larger fires, large volume of water spray should be used.
- In case of spill, recover the spilled substance as possible. After neutralizing with NH<sub>3</sub> or alcohols absorb it with sand.

[Storage]

• Store in a dry place. Keep container tightly closed in the locked place.

[Disposal]

• Dispose of contents / container to waste in accordance with local / regional / national / international regulations (to be specified).

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

SUBSTANCE/MIXTURE	: substance
CHEMICAL NAME	: Tolylene diisocyanate, Toluene diisocyanate, TDI
Component	Content METI № ISHA № CAS №
Tolylene diisocyanate	> 98 % 3-2214 Existing 26471-62-5
2,4-Tolylene diisocyanate	about 80 % 3-2214 Existing 584-84-9
2,6-Tolylene diisocyanate	about 20 % 3-2214 Existing 91-08-7
HAZADOUS INGREDIENT(s)	: 2,4-Tolylene diisocyanate 80%
	2,6-Tolylene diisocyanate 20%

#### 4. FIRST AID MEASURES

IF INHALED

- Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- Immediately call a POISON CENTER.
- · Get medical advice/attention immediately.
- If not breathing, give artificial respiration.

• If serious cough or phlegm occurs, get medical examination immediately.

## IF ON SKIN

- · Remove all contaminated clothing immediately.
- Wash off with soap and water.
- Wash skin with water stream or shower.
- If skin irritation occurs or feel unwell, get medical advice/attention.
- Take off contaminated clothing and wash before reuse.

### IF IN EYES

- Immediately rinse with fresh water for 15 minutes even if very small contact.
- Rinse carefully with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If eye irritation persists, get medical advice/attention.

### IF SWALLOWED

- Rinse the patient mouth with water and give ca. 250ml milk or water to him to drink. Do not induce vomiting. Never give anything by mouth to an unconscious person.
- Get medical advice/attention (washing of stomach) immediately.

### **5. FIRE-FIGHTING MEASURES**

SUITABLE EXTINGUISHING MEDIA:

Dry chemical powder, CO<sub>2</sub>, foam, water spray in case of larger fires

UNSUITABLE EXTINGUISHING MEDIA : Water jet

### SPECIFIC EXTINCTION METHOD

- Dry chemical powder or CO<sub>2</sub> should be used for small fire.
- In case of larger fires, large volume of water spray should be used.
- Keep surrounding areas cool by spraying water.
- Neutralize the spilled TDI after extinguished.

#### SPECIAL PROTECTIVE ACTIONS FOR FIRE-FIGHTERS

• During a fire, isocyanate vapour and hazardous gases may be generated, fireman has to wear self-contained breathing apparatus and other protective equipments.

### 6. ACCIDENTAL RELEASE MEASURES

#### PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

• Forbid any person not wearing proper protection equipments from the spilled area. Ventilate the spilled area.

#### ENVIRONMENTAL PRECAUTIONS

- Do not let this chemical enter the environment.
- METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP
  - Neutralize and absorb the spilled substance with sand. Clean the spilled area with plenty of water.
  - In case of larger spill, use countermeasure for prevention of flow and recover the spilled substance as much as possible.
  - After recovery, neutralize the spilled area.
  - · Don't close tightly container with collected material. Waste should be disposed of as described in chapter

5/13

"13. DISPOSAL CONSIDERATIONS".

• Example of neutralizing agent(wt%) : water/sodium carbonate/liquid detergent=90-95/5-10/0.2-2

# 7. HANDLING AND STORAGE

# HANDLING

TECHNICAL MEASURE

- Take measures as described in chapter "8. EXPOSURE CONTROLS / PERSONAL PROTECTION" and wear an ppropriate protective equipment.
- · Establish adequate local exhauster in the indoor working area.
- Handle under effective ventilation if product is heated.

LOCAL-VENTILATION/WHOLE-VENTILATION

• Set local exhaust or general ventilation of as described in chapter "8. EXPOSURE CONTROLS / PERSONAL PROTECTION".

NOTES

- Do not handle until all safety precautions have been read and understood.
- Do not contact, inhale and ingest.
- Wash hands thoroughly after handling.
- Use only outdoors or in well ventilated areas.
- · Avoid taking contaminated clothing out of work place.
- Do not eat, drink or smoke when using this product.

# SAFETY TREATMENT NOTES

- Pay attention to avoid contact with water or substance which react with isocyanate.
- · Always has a stock of enough personal protectors and neutralizing agent for emergency.
- Take care of falling or tumble for handling containers.

# INCOMPATIBLE MATERIALS

# • Refer to 10. STABILITY AND REACTIVITY

# STORAGE

# TECHNICAL MEASURE

- An indoor storehouse should be built with a fireproof construction and having good ventilation and its floor should be made of impermeable materials.
- Insure sufficient light for handling.

# APPROPRIATE SAFEKEEPING CONDITION

- · Keep containers tightly closed and storage in well ventilated areas.
- The storehouse should be locked.
- Once a container is opened, the container should be sealed with dry nitrogen or dry air and be closed tightly.
- Put up the sign of "Flammable" and "Off limit !".

INCOMPATIBLE SUBSTANCES

Refer to 10. STABILITY AND REACTIVITY

# PACKAGING MATERIALS

· Containers accepted Fire & Disaster Management Act and UN regulation should be used.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

FACILITY AND EQUIPMENT MEASURES

- Facilities in where this materials is handled should be structured by the perfectly closed system. Establish adequate local exhaust if vapor/mist generated.
- Operator should wear appropriate protection. Make available emergency safety shower and eye wash in the work area. The floor should be made of impermeable materials.

CONTROL LIMIT : 0.005 ppm

### OCCUPATIONAL EXPOSURE LIMITS

<ul> <li>J. Soc. Occup.Health</li> </ul>	: TWA	$0.005 \text{ ppm} (0.035 \text{ mg/m}^3) (2009)^{-8}$
	С	0.02  ppm (0.14 mg/m <sup>3</sup> )
• ACGIH	: TWA	0.001  ppm (2010) <sup>9)</sup>
	STEL	0.003 ppm

### PERSONAL PROTECTIVE EQUIPMENT

- Respiratory protection : compressed air open-circuit self-contained breathing apparatus; JIS T 8155, supplied-air respirators; JIS T 8153
- Hand protection : Protective gloves (impermeable)
- Eye protection : Protective glasses, goggles
- Skin and body protection : Protective clothing, safety boots

## HYGIENE MEASURES

- Wash hands thoroughly after handling.
- · Avoid taking contaminated clothing out of work place.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Colorless or light yellow clear liquid
Odour	: Irritating odor
pH	: No Data
Boiling point	: 251°C
Freezing point	: 11.5~13.5°C
Flash point	: 135°C
Explosion properties	: 0.9 v/v%(118°C)-9.5 v/v%(150°C)
Vapor pressure	: 0.014 hPa(20°C)
Vapor density	: 6(air=1)
Specific gravity	: about 1.22(25°C)
Solubility	: Not soluble in water
	Soluble in organic solvents(esters,ketones)
Octanol/water partition coefficient	: 3.74 (2,4-TDI 80%、2,6-TDI 20%)(estimation)
Decomposition temperature	: No Data
Viscosity	: $3mPa \cdot s(25^{\circ}C)$

### **10. STABILITY AND REACTIVITY**

### STABILITY

• Stable for normal storage and handling.

## REACTIVITY

- Exothermic reaction with amines, water and alcohols.
- Exothermic homo-polymerization itself in the presence of basic substance or a certain material compound.
- Reacts with water forming CO<sub>2</sub>.
- POSSIBILITY OF HAZARDOUS REACTIONS
  - Exothermic reaction with active hydrogen compounds (water, alcohols, amines), in closed containers, Reacts with water forming CO<sub>2</sub>, risk of bursting owing to increase of pressure.

### INCOMPATIBLE MATERIALS

· Copper and its alloy, Aluminum, Poly vinyl chloride

HAZARDOUS DECOMPOSITION PRODUCTS

• Nitrogen compounds

# 11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY [ORAL] : Not classified

2,4/2,6-TDI(80/20), LD<sub>50</sub>, oral rat 5840mg/kg (Wazeter 1964a<sup>11)</sup>), 7800mg/kg (CERI 1998<sup>12)</sup>), other similar studies available.

ACUTE TOXICITY [SKIN] : Not classified

TDI unspecified isomers, LD<sub>50</sub>, dermal, rabbit, >9400mg/kg. (Wazeter 1964b<sup>13</sup>).

ACUTE TOXICITY [INHALATION (GAS)] : Not applicable.

Liquid (GHS definition)

ACUTE TOXICITY [INHALATION (VAPOUR)] : Category 1

The saturated vapour concentration of TDI at 25°C is about 160mg/m<sup>3</sup> (22ppm). In the workplace exposure is likely to vapour only. In animal tests at the high concentrations used above the saturated vapour concentration, it may be assumed that both vapour and aerosol were present. 2,4/2,6-TDI(80/20),  $LC_{50}$ , 1hr, rat, 470mg/m<sup>3</sup> (66ppm) (Doe and Horspool 1980<sup>14</sup>),  $LC_{50}$ , 6hr, mouse, 100-140mg/m<sup>3</sup> (14-19ppm) (Mackay 1992<sup>15</sup>).

ACUTE TOXICITY [INHALATION(DUST,MIST)] : Not applicable

The saturated vapour concentration of TDI at  $25^{\circ}$ C is about 160 mg/m<sup>3</sup> (22ppm). It may be assumed that in the high exposure LC<sub>50</sub> studies both vapour and aerosol were present. For worker exposures vapour exposures are likely, see vapour section for classification.

SKIN CORROSION/IRRITATION: Category 2

(Duprat et al. 1976<sup>16</sup>) 2,4-TDI. (Knapp and Baker 1974a,b<sup>17</sup>),<sup>18</sup>) TDI unspecified. (Woolhiser et al. 1998<sup>19</sup>) TDI unspecified. EU category irritant (R38).

SERIOUS EYE DAMAGE/EYE IRRITATION : Category 2A

TDI unspecified. (Knapp and Baker 1974<sup>17)</sup>,<sup>18)</sup>, Woolhiser et al. 1998<sup>19)</sup>). EU category irritant R36). US EPA HPV, irritant.

**RESPIRATORY SENSITIZATION : Category 1** 

2,4/2,6-TDI(80/20), Respiratory sensitisation demonstrated in animal and man. (CERI hazard data collection 97-20 1998<sup>12</sup>), WHO 1987<sup>20</sup>), DFG 2003<sup>21</sup>), ACGIH 2004<sup>22</sup>), ACC 2004<sup>23</sup>), Botham et al. 1988<sup>24</sup>), Karol 1983<sup>25</sup>), Pauluhn and Mohr 1998<sup>26</sup>). EU respiratory sensitiser (R42).

SKIN SENSITIZATION: Category 1

2,4/2,6-TDI(80/20), Skin sensitisation demonstrated in animal and man.(CERI hazard data collection 97-20 1998<sup>12</sup>), WHO 1987<sup>20</sup>), DFG 2003<sup>21</sup>), ACC 2004<sup>22</sup>), van Och et al. 2000<sup>27</sup>), Zissu et al. 1998<sup>28</sup>). EU skin sensitiser (R43).

GERM CELL MUTAGENICITY : Not classified

2,4/2,6-TDI(80/20). There are no germ cell mutagenicity data. There are somatic cell mutagenicity data in vitro and in vivo and in particular mammalian studies, which are negative. (ACC 2004<sup>23</sup>), Seel et al. 1999<sup>29</sup>, Mackay 1992<sup>15</sup>), Benford and Riley 1988<sup>30</sup>, Loeser 1983<sup>31</sup>).

CARCINOGENICITY : Not classified

2,4/2,6-TDI(80/20), Carcinogenicity studies in rats and mice with inhalation exposure (the relevant route for human exposure) did not reveal any carcinogenic potential when tested up to the maximum tolerated does (Loeser 1983<sup>31</sup>). The carcinogenicity study dosing by the oral route (DHHS NTP 1986<sup>32</sup>) has been criticised for a variety of problems including exceeding the maximum tolerated dose, poor gavage technique causing deaths, and particularly inadequate storage of test material resulting in degradation of test chemical (Dieter et al. 1990<sup>33</sup>), Schulz 1985<sup>34</sup>). As the test substance dosed included degradation products, this study is considered to be invalid and thus unreliable for classification purposes. In spite of the major study deficiencies some agencies have used the data for classification: (ACGIH 2004<sup>22</sup>) classification A4, (IARC 1999<sup>35</sup>) 2B, and EU category 3 (R40). Epidemiological studies of TDI exposed workers show no increased carcinogenicity related to TDI exposure.

REPRODUCTIVE TOXICITY : Not classified

2,4/2,6 TDI (80/20), Fertility: No adverse effects in a 2-generation study in rats. No indication of selective developmental toxicity at exposure levels without maternal toxicity (Tyl et al. 1999a, $b^{36}$ , <sup>37</sup>).

SPECIFIC TARGET ORGAN TOXICITY-SINGLE EXPOSURE : Category 3 (respiratory tract irritation) For animals transient effects (Shiotsuka 1987<sup>38</sup>), Weyel et al. 1982<sup>39</sup>), Sangha and Alarie, 1979<sup>40</sup>). For people irritation is detected at 0.05–0.1ppm (Henschler 1962<sup>41</sup>).

SPECIFIC TARGET ORGAN TOXICITY-REPEATED EXPOSURE : Not classified

2,4/2,6 TDI (80/20), Comment: Lung decrement has been reported in some studies as a consequence of repeated exposure to TDI. However, this effect can only be observed after inhalation exposure in the tissue at the point of contact and does not represent systemic toxicity. It is a local effect that is already covered by respiratory irritation (TOST single exposure, Cat. 3) and respiratory sensitization (Category 1). Ott  $(2002)^{42}$  and Ott, Diller and Jolly  $(2003)^{43}$ , indicate that respiratory sensitisation may have contributed to the lung decrement reported in some studies. Therefore, it is concluded that possible lung effects do not qualify as specific target organ systemic toxicity after repeated exposure in accordance to chapter 3.9.1.6. of the GHS (UNECE  $2003^{44}$ ). In addition, all warning and safety measures for local effects as well as for acute inhalation toxicity category 1 already provide for a protection of workers and professional users that are involved in the handling of TDI.

ASPIRATION HAZARD : Not classified

Not applicable.

#### 12. ECOLOGICAL INFORMATION

AQUATIC TOXICITY[ACUTE] : Category 3

2,4/2,6-TDI(80/20), Daphnia magna, OECD 202, 48hr  $EC_{50} = 12.5$ mg/l (Tadokoro et al. 1997<sup>45</sup>). EU 52, Harmful to aquatic organisms.

#### AQUATIC TOXICITY [CHRONIC] : Not classified

2,4/2,6-TDI(80/20), Daphnia magna, OECD 211, 21day NOEL = 1.1mg/l (Cerbelaud et al. 1997<sup>46</sup>).

#### 13. DISPOSAL CONSIDERATIONS

RESIDUAL WASTE

- Product waste must be incinerated in a hazardous waste incinerator in accordance with the relevant regulation oneself or must be incinerated by waste treatment company having the official approval of regulation.
- · Notify dangerous and hazardous information thoroughly to waste treatment company.
- · Contaminated clothing also should be disposed by appropriated process after neutralizer treatment.

POLLUTION CONTAINER AND PACKING

- · Used containers could be recycled by cleaning or should be disposed accordance with official regulation.
- · In case of disposal, remove all contents

## **14. TRANSPORT INFORMATION**

INTERNATIONAL REGULATIONS

- Air : Transport in accordance with ICAO-TI/IATA-DGR.
- Sea : Transport in accordance with IMDG Code.
- UN number : 2078
- Hazard class : Class 6.1

Domestic Regulations

- Land : Follow the mode of transportation as provided in the Fire and Disaster Management Act, Industrial Safety and Health Act, Road Vehicles Act, etc.
- Sea : Follow the mode of transportation as provided in the Ships Safety Act.
- Air : Follow the mode of transportation as provided in the Aviation Law.
- Special precaution
  - Follow Fire and Disaster Management Act (Class 4-3).
  - Follow Ship Safety Act (Class 6.1).

Emergency response guideline number : 156

### **15. REGULATORY INFORMATION**

Industrial Safety and Health Act	
Ordinance on Prevention of Hazards due to Specified Chemical-	: Tolylene diisocyanate
Substances (appended table 3 of article 2 of Order)	(Category II)
Labeling substances	: Tolylene diisocyanate
(Article 57-1 of Act, appended table 2 of article 30 of Ordinance)	
Notifiable substances	: Tolylene diisocyanate
(Article 57-2 of Act, appended table 9 of article 18 of Order)	
Mutagenicity substances	: 2,6-Tolylene diisocyanate
(guideline and notification substances)	
Labor Standards Act	

m-Tolylene diisocyanate, Japan Urethane Raw Materials Association, 0331

10/13

Division Date : December 17, 2010

Illness chemical substances	: Tolylene diisocyanate	
(items 4-1 in appended table 1-2 of Ordinance 35)		
(Public notice of the Ministry of Health and Welfare N	o. 36 of March 30, 1978)	
Act on Confirmation, etc. of Release Amounts of Specific Chemical Substances in the Environment and		
Promotion of Improvements to the Management Thereof (PRTR Law)		
Class I Designated Chemical Substances	: Tolylene diisocyanate	
(Effective from October 1,2009)	(Cabinet Order №1-298)	
Fire and Disaster Management Act (Fire Service Law)		
Dangerous Substances	: Class 4-3	
Ship Safety Act	: Class 6.1	
Aviation Law	: Class 6.1	
Act Relating to the Prevention of Marine Pollution and Maritime Disaster		
Harmful liquid Substances	: Category Y	
(appended table 1 of Order)		

Air Pollution Control Act

Substances of Hazardous Air Pollutant : Tolylene diisocyanate

## **16. OTHER INFORMATION**

REFERENCES

- 1. Japan Urethane Raw Materials Association, "The overview of the polyurethane raw materials industry (2005)"
- 2. Japan Urethane Raw Materials Association, "About polyurethane raw materials Guide of the safety handling (2008)"
- 3. Japan Urethane Raw Materials Association,"Management guideline of transportation of TDI (2009)"
- Chemical Society of Japan, "Guideline of the protection against disasters TOLYLENE DIISOCYANATE (MDI) - (1996)"
- 5. Woolrich, P.F.; Am. Ind. Hyg. Assoc. J., 43, 89-97 (1982)
- 6. Duncan, B., et al.; Am Ind. Hyg. Assoc. J., 23, 447-456 (1962)
- 7. IARC Monographs (2006)
- 8. The Japan Society for Occupational Health, [Journal of Occupational Health] (2009)
- 9. 「TLVs AND BEIs」 (2010) (ACGIH)
- 10. Notification №312-2 of the Ministry of Health, Labour and Welfare (1993)
- 11. Wazeter, F. X., Keller, J. G., Buller, R. H., and Geil, R. G. (1964a). Toluene diisocyanate (TDI) and polymethylene polyphenylisocyanate (PAPI): acute toxicity studies (LD50) in male albino rats. Unpublished report by the International Research and Development Corporation.
- 12. CERI (1998). Chemicals Evaluation and Research Institute, Japan. Unpublished data.
- 13. Wazeter, F. X., Buller, R. H., and Geil, R. G. (1964b). Toluene diisocyanate (TDI) and polymethylene polyphenylisocyanate (PAPI): acute dermal toxicity studies (LD50) in thealbino rabbit. Unpublished report by the International Research and Development Corporation.
- Doe, J. E. and Horspool, G. M. (1980). Toluene di-isocyanate: acute inhalation toxicity in the rat. III Report No. 10142. International Isocyanate Institute, Manchester, UK. Available from: British Library Document Supply Centre, Boston

- Mackay, J. M. (1992). Toluene di-isocyanate: an evaluation in the mouse micronucleus test. III Report No. 10995. International Isocyanate Institute, Manchester, UK. Available from: British Library Document Supply Centre, Boston Spa, Wetherby, West Yorks.
- Spa, Wetherby, West Yorks. Duprat, P., Gradiski, D., and Marignac, B. (1976). Irritating and allergizing power of two isocyanates; toluene diisocyanate (TDI), diphenylmethane diisocyanate (MDI). Eur.J.Tox., 9, (1), 41-53.
- 17. Knapp, R. and Baker, R. (1974a). Industrial Bio-Test Laboratories. Study No. 501-05072. Unpublished.
- 18. Knapp, R. and Baker, R. (1974b). Industrial Bio-Test Laboratories. Study No. 501-05008. Unpublished.
- Woolhiser, M. R., Hayes, B. B., and Meade, B. J. (1998). A combined murine local lymph node and irritancy assay to predict sensitization and irritancy potential of chemicals. Toxicol.Methods, 8, (4), 245-56.
- WHO (1987). Toluene diisocyanates: environmental health criteria 75. International Programme on Chemical Safety. United Nations World Health Organization, United Nations Environment Programme & International Labour Organisation. Geneva, Switzerland. (ISBN 92-4-154275-6).
- DFG (2003). Toluene diisocyanate. In: 'Occupational Toxicants: Critical Data Evaluation for MAK Values and Classification of Carcinogens, Vol.20'. Ed H. Greim. Wiley-VCH, Weinheim. (ISBN 3-527-27797-8). pp. 291-338.
- 22. ACGIH (2004). Toluene-2,4 or 2,6-diisocyanate (or as a mixture). In: 'Documentation of the Threshold Limit Values and Biological Exposure Indices,' 7th ed., 2004 Supplement. American Conference of Governmental Industrial Hygienists, Inc., Cincinnati. (ISBN 1-882417-43-7).
- ACC (2004). SIDS initial assessment report for SIAM: toluene diisocyanate. International Council of Chemical Associations', High Production Volume Initiative Program [submission]. American Chemistry Council Diisocyanate Panel, 15 Jun.
- Botham, P. A., Hext, P. M., Rattray, N. J., Walsh, S. T., and Woodcock, D. R. (1988). Sensitisation of guinea pigs by inhalation exposure to low molecular weight chemicals. Toxicol.Lett., 41, 159-73.
- Karol, M. H. (1983). Concentration-dependent immunologic response to toluene diisocyanate (TDI) following inhalation exposure. Toxicol.Appl.Pharmacol., 68, 229-41.
- Pauluhn, J. and Mohr, U. (1998). Assessment of respiratory hypersensitivity in guinea pigs sensitized to toluene diisocyanate: a comparison of sensitization protocols. Inhal. Toxicol., 10, 131-54.
- 27. van Och, F. M. M., Slob, W., de Jong, W. H., Vandebriel, R. J., and van Loveren, H. (2000). A quantitative method for assessing the sensitizing potency of low molecular weight chemicals using a local lymph node assay: employment of a regression method that includes determination of the uncertainty margins. Toxicol., 146, (1), 20 Apr., 49-59.
- Zissu, D., Binet, S., and Limasset, J-C. (1998). Cutaneous sensitization to some polyisocyanate prepolymers in guinea pigs. Contact Derm., 39, 248-51.
- Seel, K., Walber, U., Herbold, B., and Kopp, R. (1999). Chemical behaviour of seven aromatic diisocyanates (toluenediisocyanates and diphenylmethanediisocyanates) under in vitro conditions in relationship to their results in the Salmonella/microsome test. Mutat.Res., 438, 109-23.
- 30. Benfor, D. J. and Riley, R. A. (1988). TDI: mutagenicity study for the detection of unscheduled DNA synthesis ex vivo in hepatocytes and lung following a single exposure of toluene diisocyanate to rats by inhalation. III Report No. 10547. International Isocyanate Institute, Manchester, UK. Available from: British Library Document Supply Centre, Boston Spa, Wetherby, West Yorks.

12/13

- Loeser, E. (1983). Long-term toxicity and carcinogenicity studies with 2,4/2,6-toluene- diisocyanate (80/20) in rats and mice. Toxicol.Lett., 15, 71-81.
- 32. DHHS NTP (1986). Toxicology and carcinogenesis studies of commercial grade 2,4(80%)- and 2,6(20%)-toluene diisocyanate in F344/N rats and B6C3F1 mice (gavage studies). US Department of Health and Human Services. National Toxicology Program. NTP TR 251; NIH Publication no. 86-2507. Research Triangle Park, NC.
- 33. Dieter, M. P., Boorman, G. A., Jameson, C. W., Matthews, H. B., and Huff, J. E. (1990). The carcinogenic activity of commercial grade toluene diisocyanate in rats and mice in relation to the metabolism of the 2,4- and 2,6-TDI isomers. Toxicol.Ind.Health, 6, (6), 599-621.
- 34. Schulz, C. O. (1985). Audit of the National Toxicology Program carcinogenesis bioassay of toluene diisocyanate. International Isocyanate Institute, Manchester, UK. III Report No. 10340. Available from: British Library Document Supply Centre, Boston Spa, etherby, West Yorks.
- 35. IARC (1999). Toluene diisocyanates. In: 'IARC Monographs on the Evaluation of Carcinogenic Risks to Humans, Vol.71, Part 2. Re-evaluation of some organic chemicals, hydrazine and hydrogen peroxide.' International Agency for Research on Cancer, Lyon. (ISBN 92-832-1271-1). pp. 865-79.
- 36. Tyl R, W., Neeper-Bradley, T. L., Fisher, L. C., Dodd, D. E., Pritts, I. M., Losco, P.E., Lyon, J. P., and Landry, T.D. (1999a). Two-generation reproductive toxicity study of inhaled toluene diisocyanate vapor in CD rats. Toxicol.Sci., 52, 258-68.
- 37. Tyl, R. W., Fisher, L. C., Dodd, D. E., Pritts, I. M., Kubena, M. F., Losco, P. E., Troup, C. M., Lyon, J. P., and Landry, T. D. (1999b). Developmental toxicity evaluation of inhaled toluene diisocyanate vapor in CD rats. Toxicol.Sci., 52, 248-57.
- Shiotsuka, R. N. (1987). Sensory irritation study of Mondur TD-80 in Sprague-Dawley rats. Toxicology Report 842. Mobay Corporation. Stilwell, KS, USA.
- Weyel, D. A., Rodney, B. S., and Alarie, Y. (1982). Sensory irritation, pulmonary irritation, and acute lethality of a polymeric isocyanate and sensory irritation of 2,6-toluene diisocyanate. Toxicol.Appl.Pharmacol., 64, 423-30.
- 40. Sangha, G. K. and Alarie, Y. (1979). Sensory irritation by toluene diisocyanate in single and repeated exposures. Toxicol.Appl.Pharmacol., 50, 533-47.
- 41. Henschler, D., Assmann, W., and Meyer, K. O. (1962). Zur Toxikologie der Toluylendiisocyanate. Arch.Toxikol., 19, 364-87.
- 42. Ott, M. G. (2002). Occupational asthma, lung function decrement, and toluene diisocyanate (TDI) exposure: a critical review of exposure-response relationships. Appl.Occup.Environ. Hyg., 17, (12), Dec., 891-901.
- Ott, M. G., Diller, W. F., and Jolly, A. T. (2003). Respiratory effects of toluene diisocyanate in the workplace: a discussion of exposure-response relationships. Crit.Rev.Toxicol., 33, (1), 1-59.
- 44. UNECE (2003). Health and environmental hazards. In: 'Globally harmonized system of classification and labelling of chemicals (GHS), Part 3. Health and environmental' UN Economic Commission for Europe. (ISBN 92-1-116927-5). Available from: <u>http://www.unece.org/trans/danger/publi/ghs/ghs\_rev00/English/GHS-PART-3e.pdf</u>

[Accessed 2 Oct., 2006].

45. Tadokoro, H., Nozaka, T., Hirata, S., and Tounai, T. (1997). Ecotoxicities of TDI and TDA to fish, algae and aquatic invertebrates. III Report No. 11217. International Isocyanate Institute, Manchester, UK.

Available from: British Library Document Supply Centre, Boston Spa, Wetherby, West Yorks.

46. Cerbelaud, E., Saugues, M., Cellier, P., and Argoud, M. (1997). Determination of the effect of TDI on the reproduction of Daphnia magna. III Report No. 11298. International Isocyanate Institute, Manchester, UK. Available from: British Library Document Supply Centre, Boston Spa, Wetherby, West Yorks.

All specifications are to be created based on the information we can get at this time may be revised by new knowledge.

The content, the physico-chemical property and so on are not a guaranteed-performance. Notes are usually aimed at handling. If special handling, usage, please Usage for safety measures.

### CONTACT

Company : Department :